MATERIAL SAFETY DATA SHEET



	1. Product and Company Identification			
Product number	103-000P			
Product name	Baker's Delight Metered Air Freshener			
Effective date	09-May-2011			
Company information	Claire Manufacturing Co. 1005 S. Westgate Drive Addison, IL 60101 United States			
Company phone	General Assistance 630-543-7600			
Emergency telephone US	800-424-9300			
Emergency telephone outside US	703-527-3887			
Version #	02			
Supersedes date11-May-2010				
	2. Hazards Identification			
Emergency overview	Flammable. Aerosol. CONTENTS UNDER PRESSURE. Harmful in contact with eyes. Prolonged exposure may cause chronic effects.			
Potential health effects				
Routes of exposure	Eye contact. Inhalation. Skin contact. Ingestion.			
Eyes	Contact may irritate or burn eyes. Eye contact may result in corneal injury.			
Skin	Health injuries are not known or expected under normal use.			
Inhalation	Intentional misuse by concentrating and inhaling the product can be harmful or fatal.			
Ingestion	Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion.			
Target organs	Central nervous system. Lungs.			
Chronic effects	Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a los of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damag May cause delayed lung injury.			
Signs and symptoms	Discomfort in the chest. Corneal damage. Narcosis. Coughing. Conjunctivitis.			
3	. Composition / Information on Ingredients			

3. Composition / Information on Ingredients

Components	CAS #	Percent
Acetone	67-64-1	60 - 70
Propane	74-98-6	10 - 15
n-Butane	106-97-8	10 - 15
Non-hazardous and other components below reportable levels		2.5 - 10

Non-hazardous and other com onents below reportable levels

4. First Aid Measures

First aid procedures		
Eye contact	Flush eyes immediately with large amounts of water. Get medical attention if irritation develops and persists.	
Skin contact	Wash off with warm water and soap. Get medical attention if irritation develops and persists.	
Inhalation	If inhalation of gas/fume/vapor/dust/mist from the material is excessive (air concentration is greater than the TLV or health effects are noticed), immediately remove the affected person(s) to fresh air. Get medical attention if symptoms persist.	
Ingestion	In the unlikely event of swallowing contact a physician or poison control center.	
5. Fire Fighting Measures		

Flammable properties

Runoff to sewer may cause fire or explosion hazard.

Protection of firefighters Protective equipment and precautions for firefighte		In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.			
	6. A	ccidental Release	Measures		
Methods for containment		Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.			
Methods for cleaning up		Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.			
		Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.			
		7. Handling and S	torage		
Handling Storage	or until s exhaust empty co Contents influence	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid contact with skin. Avoid prolonged exposure. Contents under pressure. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of			
				cool place. Keep out of the edingstuffs. Level 3 Aerosol.	
	8. Exposi	ure Controls / Pers	onal Protection		
Exposure limits					
ACGIH					
Components	CAS #	TWA	STEL	Ceiling	
Acetone	67-64-1	500 ppm	750 ppm	Not established	
Propane	74-98-6	1000 ppm	Not established	Not established	
n-Butane	106-97-8	1000 ppm	Not established	Not established	
OSHA					
Components	CAS #	TWA	STEL	Ceiling	
Acetone	67-64-1	1000 ppm	Not established	Not established	
Propane	74-98-6	1000 ppm	Not established	Not established	
Personal protective equipmer	nt				
Eye / face protection		et in eyes. Chemical doo	gles are recommended.		
Skin protection	Wear appropriate chemical resistant clothing.				
Respiratory protection	• •		trations above the exposur	e limit they must use	

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	82.4 °F (27.8 °C) estimated
Color	Not established.
Density	0.7124 g/cm3 estimated
Flammability (HOC)	32.5519 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Freezing point	Not available
Odor	fruity
pН	Not applicable
Physical state	Liquid.

Pressure Solubility	45 - 65 psig @ 70f Partially			
Specific gravity	cific gravity 0.7125 estimated			
	10. Chemical Stability & Reactivity Information			
Chemical stability	Risk of ignition. Material is stable under normal conditions.			
Conditions to avoid	Heat, flames and sparks.			
Hazardous decomposition produ	cts No hazardous decomposition products are known.			
	11. Toxicological Information			
Component analysis - LD50 Toxicology Data - Selected LD50 Acetone n-Butane Propane	bs and LC50s 67-64-1 Oral LD50 Rat 5800 mg/kg 106-97-8 Inhalation LC50 Rat 658 mg/L 4 h 74-98-6 Inhalation LC50 Rat 658 mg/L 4 h			
	12. Ecological Information			
Ecotoxicity	Contains a substance which causes risk of hazardous effects to the environment.			
	13. Disposal Considerations			
Waste codes	D001: Waste Flammable material with a flash point <140 F			
Disposal instructions	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.			
	14. Transport Information			
Department of Transportation (D0	OT) Requirements			
Basic shipping requirements	:			
Proper shipping name	Consumer commodity			
Hazard class	ORM-D			
Subsidiary hazard class	None			
Additional information:				
Packaging exceptions	156, 306			
Packaging non bulk	156, 306			
Packaging bulk	None			
MDG				
Basic shipping requirements				
Proper shipping name	AEROSOLS			
Hazard class	2.1			
UN number	1950			
Additional information:				
Packaging exceptions	LTD QTY			
Labels required	None 2			

ΙΑΤΑ

Basic shipping requirements:	
Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



	-	15. Regulatory Information			
US federal regulations		This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.			
Occupational Safety and Health	Administratio	n (OSHA)			
29 CFR 1910.1200 hazardous chemical	s Yes				
CERCLA (Superfund) reportable	quantity				
Acetone: 5000.0000					
Superfund Amendments and Rea	authorization	Act of 1986 (SARA)			
Section 302 extremely hazardous substance	ction 302 extremely No				
Section 311 hazardous chen	nical Yes				
Hazard categories (311/312)	Delayed Fire Haz Pressur	ate Hazard - Yes Hazard - No card - Yes e Hazard - Yes ty Hazard - No			
Inventory status					
Country(s) or region	Inventory na	ame	On inventory (yes/no)*		
China	=	Existing Chemical Substances in China (IECSC)	Yes		
Europe					
Europe European List of Notified Chemical Substances (ELINCS)			No		
Japan	Inventory of	Existing and New Chemical Substances (ENCS)	Yes		
Korea	Existing Che	micals List (ECL)	No		
United States & Puerto Rico	Toxic Substa	Toxic Substances Control Act (TSCA) Inventory Yes			
A "Yes" indicates that all compone	ents of this prod	uct comply with the inventory requirements administered I	by the governing country(s)		
State regulations					
U.S Pennsylvania - RTK (Righ	t to Know) List				
Acetone	67-64-1	Environmental hazard			
n-Butane Propane	106-97-8 74-98-6	Present Present			
	14 00 0	1 reserve			
		16. Other Information			
Further information	HMIS®	is a registered trade and service mark of the NPCA			
HMIS [®] ratings	Health: 1				
-	Flammability: 4				
	•	I hazard: 0			
Disclaimer	knowled designe disposal informat material in the te	rmation provided in this Safety Data Sheet is correct ge, information and belief at the date of its publication d only as a guidance for safe handling, use, process and release and is not to be considered a warranty ion relates only to the specific material designated a used in combination with any other materials or in att. The information in the sheet was written based of the currently available.	on. The information given is sing, storage, transportation, or quality specification. The and may not be valid for such any process, unless specified		
SDS sections updated Product and Company Identification: Product Review					
Prepared by Regulatory Compliance					